

9. 伸縮可撓管・ヴィクトリックジョイント

スーパーボール

コスモ工機(株)

ダクティル鑄鉄製ボール式伸縮可撓管 離脱防止性能A級(タイロッド付標準仕様)

GX形用

GX形受口 × GX形受口

■EB-UG × UG

単位:円

呼び径	偏芯量(mm)			
	100	200	300	400
75	689,000	750,000	802,000	873,000
100	817,000	870,000	935,000	1,018,000
150	988,000	1,140,000	1,258,000	1,415,000
200	1,216,000	1,415,000	1,537,000	1,698,000
250	1,604,000	1,780,000	1,961,000	2,405,000
300	1,830,000	2,142,000	2,372,000	2,748,000
400	2,811,000	3,213,000	3,577,000	4,065,000

フランジ × GX形受口

■EB-F × UG

単位:円

呼び径	偏芯量(mm)			
	100	200	300	400
75	534,000	595,000	660,000	700,000
100	660,000	722,000	779,000	842,000
150	833,000	986,000	1,101,000	1,220,000
200	1,055,000	1,250,000	1,368,000	1,494,000
250	1,326,000	1,550,000	1,728,000	2,113,000
300	1,531,000	1,844,000	2,069,000	2,329,000
400	2,327,000	2,680,000	3,106,000	3,520,000

GX形受口 × GX形挿口

■EB-UG × SG

単位:円

呼び径	偏芯量(mm)			
	100	200	300	400
75	634,000	694,000	759,000	815,000
100	774,000	815,000	878,000	961,000
150	934,000	1,086,000	1,203,000	1,346,000
200	1,164,000	1,363,000	1,483,000	1,660,000
250	1,583,000	1,719,000	1,900,000	2,313,000
300	1,720,000	2,037,000	2,311,000	2,697,000
400	2,638,000	3,035,000	3,399,000	3,871,000

フランジ × GX形挿口

■EB-F × SG

単位:円

呼び径	偏芯量(mm)			
	100	200	300	400
75	481,000	545,000	593,000	649,000
100	606,000	660,000	723,000	793,000
150	777,000	933,000	1,045,000	1,155,000
200	1,002,000	1,203,000	1,318,000	1,473,000
250	1,249,000	1,493,000	1,663,000	2,066,000
300	1,425,000	1,736,000	1,995,000	2,235,000
400	2,151,000	2,496,000	2,923,000	3,322,000

GX形挿口 × GX形挿口

■EB-SG × SG

単位:円

呼び径	偏芯量(mm)			
	100	200	300	400
75	580,000	639,000	703,000	760,000
100	711,000	759,000	824,000	902,000
150	878,000	1,030,000	1,147,000	1,274,000
200	1,115,000	1,313,000	1,434,000	1,626,000
250	1,397,000	1,662,000	1,838,000	2,228,000
300	1,613,000	1,928,000	2,240,000	2,621,000
400	2,464,000	2,853,000	3,219,000	3,677,000

フランジ:7.5K仕様です

1.0MPa以上のタイロッド付に関してはお問合せ下さい

フランジ接合部付属品は含まれておりません

GX型受口仕様には、ゴム輪・ストップ・ロックリングが含まれております

ダクティル鋳鉄製ボール式伸縮可撓管 離脱防止性能A級(タイロッド付標準仕様)
K形用

フランジ × フランジ

■EB-F × F

単位:円

呼び径	偏芯量(mm)				
	100	200	300	400	500
50	204,000	248,000	295,000	-	-
75	321,000	380,000	424,000	506,000	-
100	436,000	479,000	531,000	583,000	-
150	580,000	714,000	799,000	886,000	-
200	767,000	912,000	1,023,000	1,132,000	-
250	935,000	1,137,000	1,268,000	1,566,000	-
300	1,078,000	1,279,000	1,473,000	1,751,000	-
350	1,262,000	1,558,000	1,889,000	2,200,000	-
400	1,744,000	2,031,000	2,501,000	2,824,000	-
450	2,184,000	2,564,000	2,978,000	3,408,000	-
500	2,367,000	2,851,000	3,317,000	3,806,000	-
600	3,194,000	3,631,000	4,244,000	5,710,000	-
700	-	6,322,000	6,688,000	7,173,000	7,945,000
800	-	7,322,000	7,585,000	8,533,000	9,600,000
900	-	9,314,000	9,864,000	10,948,000	12,231,000
1000	-	14,427,000	15,309,000	16,260,000	17,835,000

K形受口 × K形受口

■EB-U × U

単位:円

呼び径	偏芯量(mm)				
	100	200	300	400	500
75	321,000	380,000	424,000	459,000	-
100	438,000	486,000	537,000	580,000	-
150	595,000	716,000	802,000	870,000	-
200	785,000	920,000	1,031,000	1,107,000	-
250	963,000	1,152,000	1,280,000	1,520,000	-
300	1,108,000	1,313,000	1,471,000	1,726,000	-
350	1,355,000	1,583,000	1,914,000	2,292,000	-
400	1,791,000	2,094,000	2,518,000	2,907,000	-
450	2,290,000	2,639,000	3,087,000	3,502,000	-
500	2,569,000	2,957,000	3,403,000	3,944,000	-
600	3,308,000	3,748,000	4,399,000	5,024,000	-
700	-	6,541,000	6,782,000	7,269,000	8,043,000
800	-	7,563,000	7,684,000	8,628,000	9,698,000
900	-	9,813,000	10,637,000	11,462,000	12,896,000
1000	-	15,082,000	16,014,000	17,016,000	18,888,000

フランジ × K形挿口

■EB-F × S

単位:円

呼び径	偏芯量(mm)				
	100	200	300	400	500
75	314,000	374,000	416,000	479,000	-
100	430,000	474,000	525,000	575,000	-
150	565,000	700,000	785,000	864,000	-
200	760,000	908,000	1,021,000	1,117,000	-
250	900,000	1,107,000	1,233,000	1,537,000	-
300	1,021,000	1,272,000	1,465,000	1,729,000	-
350	1,341,000	1,536,000	1,866,000	2,186,000	-
400	1,681,000	2,005,000	2,410,000	2,765,000	-
450	2,253,000	2,550,000	2,976,000	3,379,000	-
500	2,422,000	2,841,000	3,334,000	3,794,000	-
600	3,141,000	3,616,000	4,236,000	4,805,000	-
700	-	6,259,000	6,625,000	7,110,000	7,887,000
800	-	7,250,000	7,514,000	8,460,000	9,526,000
900	-	9,195,000	9,881,000	10,836,000	12,151,000
1000	-	14,318,000	15,224,000	16,202,000	17,877,000

K形受口 × K形挿口

■EB-U × S

単位:円

呼び径	偏芯量(mm)				
	100	200	300	400	500
75	314,000	374,000	416,000	457,000	-
100	431,000	475,000	526,000	573,000	-
150	571,000	702,000	788,000	857,000	-
200	760,000	908,000	1,021,000	1,106,000	-
250	931,000	1,135,000	1,266,000	1,515,000	-
300	1,074,000	1,276,000	1,467,000	1,717,000	-
350	1,278,000	1,546,000	1,878,000	2,223,000	-
400	1,722,000	2,017,000	2,431,000	2,808,000	-
450	2,184,000	2,550,000	2,993,000	3,414,000	-
500	2,473,000	2,864,000	3,398,000	3,843,000	-
600	3,169,000	3,641,000	4,539,000	4,877,000	-
700	-	6,310,000	6,674,000	7,160,000	7,934,000
800	-	7,302,000	7,563,000	8,507,000	9,574,000
900	-	9,445,000	10,269,000	11,095,000	12,482,000
1000	-	14,647,000	15,576,000	16,580,000	18,404,000

フランジ × K形受口

■EB-F × U

単位:円

呼び径	偏芯量(mm)				
	100	200	300	400	500
75	321,000	380,000	424,000	483,000	-
100	437,000	484,000	534,000	581,000	-
150	581,000	715,000	801,000	877,000	-
200	769,000	917,000	1,029,000	1,119,000	-
250	938,000	1,144,000	1,272,000	1,543,000	-
300	1,080,000	1,285,000	1,478,000	1,737,000	-
350	1,282,000	1,571,000	1,900,000	2,241,000	-
400	1,757,000	2,082,000	2,514,000	2,860,000	-
450	2,215,000	2,577,000	3,160,000	3,464,000	-
500	2,486,000	2,878,000	3,441,000	3,864,000	-
600	3,249,000	3,721,000	4,323,000	4,895,000	-
700	-	6,492,000	6,733,000	7,218,000	7,996,000
800	-	7,371,000	7,633,000	8,580,000	9,648,000
900	-	9,563,000	10,250,000	11,206,000	12,565,000
1000	-	14,753,000	15,662,000	16,639,000	18,361,000

K形挿口 × K形挿口

■EB-S × S

単位:円

呼び径	偏芯量(mm)				
	100	200	300	400	500
75	307,000	365,000	408,000	454,000	-
100	387,000	465,000	515,000	564,000	-
150	554,000	689,000	773,000	842,000	-
200	754,000	899,000	1,012,000	1,104,000	-
250	917,000	1,122,000	1,250,000	1,507,000	-
300	1,010,000	1,260,000	1,452,000	1,708,000	-
350	1,385,000	1,510,000	1,841,000	2,153,000	-
400	1,729,000	1,982,000	2,321,000	2,693,000	-
450	2,141,000	2,519,000	2,929,000	3,330,000	-
500	2,422,000	2,830,000	3,298,000	3,758,000	-
600	3,072,000	3,581,000	4,186,000	4,730,000	-
700	-	6,201,000	6,564,000	7,050,000	7,827,000
800	-	7,182,000	7,442,000	8,388,000	9,453,000
900	-	9,075,000	9,898,000	10,725,000	12,068,000
1000	-	14,210,000	15,138,000	16,144,000	17,920,000

※その他の口径についてはお問い合わせ下さい
フランジ:7.5K仕様です
1.0MPa以上のタイロッド付に関してはお問合せ下さい
接合部付属品は含まれておりません

ダクティル 鋳鉄製ボール式伸縮可撓管 離脱防止性能A級(タイロッド付標準仕様)
NS形用

フランジ × NS形挿口

■EB-F × SN

単位:円

呼び径	偏芯量(mm)				
	100	200	300	400	500
75	418,000	473,000	517,000	564,000	-
100	526,000	575,000	627,000	690,000	-
150	674,000	811,000	908,000	1,004,000	-
200	871,000	1,046,000	1,146,000	1,280,000	-
250	1,086,000	1,298,000	1,449,000	1,797,000	-
300	1,239,000	1,509,000	1,735,000	1,945,000	-
350	1,441,000	1,774,000	2,094,000	2,464,000	-
400	1,890,000	2,211,000	2,619,000	2,983,000	-
450	2,470,000	2,760,000	3,282,000	3,682,000	-
500	2,805,000	3,255,000	3,710,000	4,104,000	-
600	3,592,000	4,139,000	4,686,000	5,159,000	-
700	-	6,896,000	7,536,000	8,241,000	9,176,000
800	-	8,300,000	9,032,000	9,622,000	11,749,000

NS形受口 × NS形挿口

■EB-UN × SN

単位:円

呼び径	偏芯量(mm)				
	100	200	300	400	500
75	550,000	605,000	660,000	708,000	-
100	673,000	708,000	765,000	837,000	-
150	812,000	944,000	1,046,000	1,169,000	-
200	1,013,000	1,184,000	1,289,000	1,443,000	-
250	1,376,000	1,495,000	1,653,000	2,012,000	-
300	1,496,000	1,771,000	2,010,000	2,345,000	-
350	1,762,000	2,078,000	2,396,000	2,693,000	-
400	2,202,000	2,565,000	2,933,000	3,297,000	-
450	2,901,000	3,311,000	3,719,000	4,129,000	-
500	3,545,000	3,999,000	4,455,000	4,914,000	-
600	4,453,000	5,003,000	5,551,000	6,097,000	-
700	-	8,053,000	8,694,000	9,335,000	10,231,000
800	-	9,776,000	10,508,000	11,241,000	13,132,000

フランジ × NS形受口

■EB-F × UN

単位:円

呼び径	偏芯量(mm)				
	100	200	300	400	500
75	464,000	519,000	575,000	608,000	-
100	575,000	626,000	677,000	732,000	-
150	724,000	857,000	956,000	1,060,000	-
200	917,000	1,087,000	1,190,000	1,299,000	-
250	1,165,000	1,361,000	1,516,000	1,850,000	-
300	1,344,000	1,617,000	1,813,000	2,038,000	-
350	1,576,000	1,880,000	2,212,000	2,529,000	-
400	2,060,000	2,422,000	2,789,000	3,152,000	-
450	2,644,000	3,022,000	3,463,000	3,872,000	-
500	3,194,000	3,650,000	4,104,000	4,562,000	-
600	4,054,000	4,602,000	5,150,000	5,698,000	-
700	-	6,912,000	7,493,000	8,074,000	10,735,000
800	-	8,082,000	8,747,000	9,413,000	11,219,000

NS形挿口 × NS形挿口

■EB-SN × SN

単位:円

呼び径	偏芯量(mm)				
	100	200	300	400	500
75	504,000	556,000	613,000	663,000	-
100	618,000	660,000	716,000	784,000	-
150	765,000	897,000	998,000	1,107,000	-
200	970,000	1,142,000	1,247,000	1,414,000	-
250	1,216,000	1,445,000	1,599,000	1,937,000	-
300	1,401,000	1,676,000	1,947,000	2,279,000	-
350	1,641,000	1,958,000	2,275,000	2,592,000	-
400	2,034,000	2,324,000	2,763,000	3,126,000	-
450	2,721,000	3,026,000	3,518,000	3,948,000	-
500	3,150,000	3,607,000	4,062,000	4,455,000	-
600	3,991,000	4,539,000	5,086,000	5,634,000	-
700	-	7,345,000	7,985,000	8,627,000	9,486,000
800	-	9,187,000	9,919,000	10,651,000	12,513,000

NS形受口 × NS形受口

■EB-UN × UN

単位:円

呼び径	偏芯量(mm)				
	100	200	300	400	500
75	598,000	651,000	697,000	759,000	-
100	711,000	757,000	813,000	884,000	-
150	859,000	992,000	1,095,000	1,230,000	-
200	1,056,000	1,230,000	1,335,000	1,478,000	-
250	1,395,000	1,547,000	1,705,000	2,091,000	-
300	1,592,000	1,862,000	2,063,000	2,389,000	-
350	1,881,000	2,200,000	2,518,000	2,834,000	-
400	2,373,000	2,736,000	3,101,000	3,464,000	-
450	3,081,000	3,490,000	3,898,000	4,309,000	-
500	3,939,000	4,395,000	4,852,000	5,308,000	-
600	4,917,000	5,466,000	6,014,000	6,562,000	-
700	-	8,760,000	9,400,000	10,039,000	11,089,000
800	-	10,366,000	11,098,000	11,829,000	13,812,000

※その他の口径についてはお問い合わせ下さい
フランジ:7.5K仕様です
1.0MPa以上のタイロッド付に関してはお問合せ下さい
接合部付属品は含まれておりません

タイ・フレックス(TF-80W)GX形

大成機工(株)

FCD製・伸縮可撓管

離脱防止性能A級

単位:円

呼び径	接合形式	ダブル型(TF-80W)			
		偏心量100mm	偏心量200mm	偏心量300mm	偏心量400mm
75	F x U	515,000	585,000	655,000	725,000
	F x S	466,000	536,000	606,000	676,000
	U x U	702,000	772,000	842,000	912,000
	U x S	653,000	723,000	793,000	863,000
	S x S	604,000	674,000	744,000	814,000
100	F x U	620,000	713,000	806,000	899,000
	F x S	567,000	660,000	753,000	846,000
	U x U	826,000	919,000	1,012,000	1,105,000
	U x S	773,000	866,000	959,000	1,052,000
	S x S	720,000	813,000	906,000	999,000
150	F x U	843,000	978,000	1,113,000	1,248,000
	F x S	781,000	916,000	1,051,000	1,186,000
	U x U	1,064,000	1,199,000	1,334,000	1,469,000
	U x S	1,002,000	1,137,000	1,272,000	1,407,000
	S x S	940,000	1,075,000	1,210,000	1,345,000
200	F x U	1,040,000	1,224,000	1,408,000	1,592,000
	F x S	1,010,000	1,194,000	1,378,000	1,562,000
	U x U	1,304,000	1,488,000	1,672,000	1,856,000
	U x S	1,274,000	1,458,000	1,642,000	1,826,000
	S x S	1,244,000	1,428,000	1,612,000	1,796,000
250	F x U	1,300,000	1,532,000	1,764,000	1,996,000
	F x S	1,231,000	1,463,000	1,695,000	1,927,000
	U x U	1,635,000	1,867,000	2,099,000	2,331,000
	U x S	1,566,000	1,798,000	2,030,000	2,262,000
	S x S	1,497,000	1,729,000	1,961,000	2,193,000
300	F x U	1,515,000	1,792,000	2,069,000	2,346,000
	F x S	1,410,000	1,687,000	1,964,000	2,241,000
	U x U	1,943,000	2,220,000	2,497,000	2,774,000
	U x S	1,838,000	2,115,000	2,392,000	2,669,000
	S x S	1,733,000	2,010,000	2,287,000	2,564,000
400	F x U	2,371,000	2,741,000	3,111,000	3,481,000
	F x S	2,182,000	2,552,000	2,922,000	3,292,000
	U x U	2,939,000	3,309,000	3,679,000	4,049,000
	U x S	2,750,000	3,120,000	3,490,000	3,860,000
	S x S	2,561,000	2,931,000	3,301,000	3,671,000



※F=フランジ、U=受口(GX形)、S=挿口(GX形)

※上記価格には接合用附属品は含んでおりません。

※フランジ:7.5K仕様、高圧使用の場合は別途お問合せ下さい。

タイ・フレックス(TF-80W)K形

大成機工(株)

単位:円

FCD製・伸縮可撓管 離脱防止性能A級

呼び径	接合形式	ダブル型(TF-80W)			
		偏心量100mm	偏心量200mm	偏心量300mm	偏心量400mm
50	F x F	210,000	255,000	300,000	-
75	F x F	328,000	398,000	468,000	538,000
	F x U	336,000	406,000	476,000	546,000
	F x S	324,000	394,000	464,000	534,000
	U x U	344,000	414,000	484,000	554,000
	U x S	332,000	402,000	472,000	542,000
	S x S	320,000	390,000	460,000	530,000
	100	F x F	414,000	507,000	600,000
F x U		417,000	510,000	603,000	696,000
F x S		402,000	495,000	588,000	681,000
U x U		420,000	513,000	606,000	699,000
U x S		405,000	498,000	591,000	684,000
S x S		390,000	483,000	576,000	669,000
150		F x F	622,000	757,000	892,000
	F x U	624,000	759,000	894,000	1,029,000
	F x S	599,000	734,000	869,000	1,004,000
	U x U	626,000	761,000	896,000	1,031,000
	U x S	601,000	736,000	871,000	1,006,000
	S x S	576,000	711,000	846,000	981,000
	200	F x F	776,000	960,000	1,144,000
F x U		795,000	979,000	1,163,000	1,347,000
F x S		776,000	960,000	1,144,000	1,328,000
U x U		814,000	998,000	1,182,000	1,366,000
U x S		795,000	979,000	1,163,000	1,347,000
S x S		776,000	960,000	1,144,000	1,328,000
250		F x F	965,000	1,197,000	1,429,000
	F x U	978,000	1,210,000	1,442,000	1,674,000
	F x S	954,000	1,186,000	1,418,000	1,650,000
	U x U	991,000	1,223,000	1,455,000	1,687,000
	U x S	967,000	1,199,000	1,431,000	1,663,000
	S x S	943,000	1,175,000	1,407,000	1,639,000
	300	F x F	1,087,000	1,364,000	1,641,000
F x U		1,115,000	1,392,000	1,669,000	1,946,000
F x S		1,054,000	1,331,000	1,608,000	1,885,000
U x U		1,143,000	1,420,000	1,697,000	1,974,000
U x S		1,082,000	1,359,000	1,636,000	1,913,000
S x S		1,021,000	1,298,000	1,575,000	1,852,000
350		F x F	1,323,000	1,646,000	1,969,000
	F x U	1,364,000	1,687,000	2,010,000	2,333,000
	F x S	1,295,000	1,618,000	1,941,000	2,264,000
	U x U	1,405,000	1,728,000	2,051,000	2,374,000
	U x S	1,336,000	1,659,000	1,982,000	2,305,000
	S x S	1,267,000	1,590,000	1,913,000	2,236,000
400	F x F	1,803,000	2,173,000	2,543,000	2,913,000
	F x U	1,840,000	2,210,000	2,580,000	2,950,000
	F x S	1,735,000	2,105,000	2,475,000	2,845,000
	U x U	1,877,000	2,247,000	2,617,000	2,987,000
	U x S	1,772,000	2,142,000	2,512,000	2,882,000
	S x S	1,667,000	2,037,000	2,407,000	2,777,000
450	F x F	2,303,000	2,720,000	3,137,000	3,554,000
	F x U	2,348,000	2,765,000	3,182,000	3,599,000
	F x S	2,251,000	2,668,000	3,085,000	3,502,000
	U x U	2,393,000	2,810,000	3,227,000	3,644,000
	U x S	2,296,000	2,713,000	3,130,000	3,547,000
	S x S	2,199,000	2,616,000	3,033,000	3,450,000

呼び径	接合形式	ダブル型(TF-80W)			
		偏心量100mm	偏心量200mm	偏心量300mm	偏心量400mm
500	F x F	2,564,000	3,027,000	3,490,000	3,953,000
	F x U	2,634,000	3,097,000	3,560,000	4,023,000
	F x S	2,537,000	3,000,000	3,463,000	3,926,000
	U x U	2,704,000	3,167,000	3,630,000	4,093,000
	U x S	2,607,000	3,070,000	3,533,000	3,996,000
	S x S	2,510,000	2,973,000	3,436,000	3,899,000
	600	F x F	3,334,000	3,891,000	4,448,000
F x U		3,398,000	3,955,000	4,512,000	5,069,000
F x S		3,284,000	3,841,000	4,398,000	4,955,000
U x U		3,462,000	4,019,000	4,576,000	5,133,000
U x S		3,348,000	3,905,000	4,462,000	5,019,000
S x S		3,234,000	3,791,000	4,348,000	4,905,000
700		F x F	-	6,673,000	7,324,000
	F x U	-	6,785,000	7,436,000	8,087,000
	F x S	-	6,608,000	7,259,000	7,910,000
	U x U	-	6,897,000	7,548,000	8,199,000
	U x S	-	6,720,000	7,371,000	8,022,000
	S x S	-	6,543,000	7,194,000	7,845,000
	800	F x F	-	7,745,000	8,492,000
F x U		-	7,890,000	8,637,000	9,384,000
F x S		-	7,654,000	8,401,000	9,148,000
U x U		-	8,035,000	8,782,000	9,529,000
U x S		-	7,799,000	8,546,000	9,293,000
S x S		-	7,563,000	8,310,000	9,057,000
900		F x F	-	9,602,000	10,441,000
	F x U	-	9,840,000	10,679,000	11,518,000
	F x S	-	9,460,000	10,299,000	11,138,000
	U x U	-	10,078,000	10,917,000	11,756,000
	U x S	-	9,698,000	10,537,000	11,376,000
	S x S	-	9,318,000	10,157,000	10,996,000
	1000	F x F	-	14,826,000	15,763,000
1100	F x F	-	-	-	20,601,000
1200	F x F	-	-	-	24,923,000
1350	F x F	-	-	-	31,336,000
1500	F x F	-	-	-	36,023,000

※F=フランジ、U=受口、S=挿口(K型、T型)

タイ・フレックス(TF-80W)NS形

大成機工(株)

FCD製・伸縮可撓管 離脱防止性能A級

単位:円

呼び径	接合形式	ダブル型(TF-80W)			
		偏心量100mm	偏心量200mm	偏心量300mm	偏心量400mm
75	F x U	462,000	532,000	602,000	672,000
	F x S	416,000	486,000	556,000	626,000
	U x U	596,000	666,000	736,000	806,000
	U x S	550,000	620,000	690,000	760,000
	S x S	504,000	574,000	644,000	714,000
100	F x U	556,000	649,000	742,000	835,000
	F x S	507,000	600,000	693,000	786,000
	U x U	698,000	791,000	884,000	977,000
	U x S	649,000	742,000	835,000	928,000
	S x S	600,000	693,000	786,000	879,000
150	F x U	754,000	889,000	1,024,000	1,159,000
	F x S	698,000	833,000	968,000	1,103,000
	U x U	886,000	1,021,000	1,156,000	1,291,000
	U x S	830,000	965,000	1,100,000	1,235,000
	S x S	774,000	909,000	1,044,000	1,179,000
200	F x U	929,000	1,113,000	1,297,000	1,481,000
	F x S	901,000	1,085,000	1,269,000	1,453,000
	U x U	1,082,000	1,266,000	1,450,000	1,634,000
	U x S	1,054,000	1,238,000	1,422,000	1,606,000
	S x S	1,026,000	1,210,000	1,394,000	1,578,000
250	F x U	1,162,000	1,394,000	1,626,000	1,858,000
	F x S	1,099,000	1,331,000	1,563,000	1,795,000
	U x U	1,359,000	1,591,000	1,823,000	2,055,000
	U x S	1,296,000	1,528,000	1,760,000	1,992,000
	S x S	1,233,000	1,465,000	1,697,000	1,929,000
300	F x U	1,351,000	1,628,000	1,905,000	2,182,000
	F x S	1,255,000	1,532,000	1,809,000	2,086,000
	U x U	1,615,000	1,892,000	2,169,000	2,446,000
	U x S	1,519,000	1,796,000	2,073,000	2,350,000
	S x S	1,423,000	1,700,000	1,977,000	2,254,000
350	F x U	1,631,000	1,954,000	2,277,000	2,600,000
	F x S	1,510,000	1,833,000	2,156,000	2,479,000
	U x U	1,939,000	2,262,000	2,585,000	2,908,000
	U x S	1,818,000	2,141,000	2,464,000	2,787,000
	S x S	1,697,000	2,020,000	2,343,000	2,666,000
400	F x U	2,123,000	2,493,000	2,863,000	3,233,000
	F x S	1,949,000	2,319,000	2,689,000	3,059,000
	U x U	2,443,000	2,813,000	3,183,000	3,553,000
	U x S	2,269,000	2,639,000	3,009,000	3,379,000
	S x S	2,095,000	2,465,000	2,835,000	3,205,000
450	F x U	2,748,000	3,165,000	3,582,000	3,999,000
	F x S	2,564,000	2,981,000	3,398,000	3,815,000
	U x U	3,193,000	3,610,000	4,027,000	4,444,000
	U x S	3,009,000	3,426,000	3,843,000	4,260,000
	S x S	2,825,000	3,242,000	3,659,000	4,076,000

呼び径	接合形式	ダブル型(TF-80W)			
		偏心量100mm	偏心量200mm	偏心量300mm	偏心量400mm
500	F x U	3,322,000	3,785,000	4,248,000	4,711,000
	F x S	2,921,000	3,384,000	3,847,000	4,310,000
	U x U	4,080,000	4,543,000	5,006,000	5,469,000
	U x S	3,679,000	4,142,000	4,605,000	5,068,000
	S x S	3,278,000	3,741,000	4,204,000	4,667,000
600	F x U	4,213,000	4,770,000	5,327,000	5,884,000
	F x S	3,742,000	4,299,000	4,856,000	5,413,000
	U x U	5,092,000	5,649,000	6,206,000	6,763,000
	U x S	4,621,000	5,178,000	5,735,000	6,292,000
	S x S	4,150,000	4,707,000	5,264,000	5,821,000
700	F x U	-	7,851,000	8,502,000	9,153,000
	F x S	-	7,131,000	7,782,000	8,433,000
	U x U	-	9,029,000	9,680,000	10,331,000
	U x S	-	8,309,000	8,960,000	9,611,000
	S x S	-	7,589,000	8,240,000	8,891,000
800	F x U	-	9,247,000	9,994,000	10,741,000
	F x S	-	8,647,000	9,394,000	10,141,000
	U x U	-	10,749,000	11,496,000	12,243,000
	U x S	-	10,149,000	10,896,000	11,643,000
	S x S	-	9,549,000	10,296,000	11,043,000
900	F x U	-	11,532,000	12,371,000	13,210,000
	F x S	-	10,571,000	11,410,000	12,249,000
	U x U	-	13,462,000	14,301,000	15,140,000
	U x S	-	12,501,000	13,340,000	14,179,000
	S x S	-	11,540,000	12,379,000	13,218,000
1000	F x U	-	17,630,000	18,567,000	19,504,000
	F x S	-	16,328,000	17,265,000	18,202,000
	U x U	-	20,434,000	21,371,000	22,308,000
	U x S	-	19,132,000	20,069,000	21,006,000
	S x S	-	17,830,000	18,767,000	19,704,000

※F=フランジ、U=受口、S=挿口(NS形)

単位:円

品名 サイズ	クローザージョイント				クローザージョイント(低圧用)	
	CL-A 標準型 (両ベベル)		CL-A100mm偏心型 (両ベベル)		Σ0両ベベル100mm偏心型	
	両間	価格	両間	価格	面間	価格
50	-	-	-	-	950	276,000
80	800	572,000	1150	680,000	950	359,000
100	800	612,000	1150	734,000	950	412,000
125	800	680,000	1150	796,000	950	490,000
150	800	750,000	1150	870,000	950	610,000
200	800	807,000	1150	948,000	1000	687,000
250	800	925,000	1150	1,094,000	1000	793,000
300	800	1,103,000	1600	1,246,000	1000	917,000
350	800	1,203,000	1600	1,406,000	1050	1,042,000
400	800	1,427,000	1600	1,606,000	1050	1,196,000
450	800	1,637,000	1600	1,845,000	1050	1,346,000
500	900	1,853,000	1700	2,119,000	1100	1,556,000
600	900	2,193,000	1700	2,462,000	1150	1,831,000
700	1000	2,662,000	1800	2,944,000	1200	2,173,000
800	1100	3,137,000	1800	3,552,000	1200	2,534,000
900	1100	3,542,000	1800	3,916,000	1200	2,913,000
1000	1200	4,558,000	1900	5,022,000	1200	3,521,000

クローザージョイント(CL-A型)



クローザージョイント(Σ型)



単位:円

品名	フランジアダプター		スリーブジョイント			スリーブジョイント (エポキシ樹脂粉体塗装)		
	FA-CB型両フランジ					VD型	VDL型	RD型
サイズ	両間	価格				ボルト SUS304		
50	500	550,000	75,600	-	-	-	-	-
65	500	593,000	78,000	93,000	-	118,000	150,000	-
80	500	618,000	93,000	107,000	-	136,000	170,000	-
100	500	660,000	99,000	119,000	-	158,000	193,000	-
125	500	728,000	134,000	154,000	-	203,000	252,000	-
150	500	787,000	165,000	197,000	-	250,000	306,000	-
200	500	967,000	201,000	245,000	-	304,000	392,000	-
250	500	1,070,000	232,000	277,000	-	352,000	436,000	-
300	500	1,186,000	264,000	315,000	-	388,000	488,000	-
350	500	1,345,000	-	-	407,000	-	-	553,000
400	500	1,497,000	-	-	479,000	-	-	652,000
450	500	1,688,000	-	-	536,000	-	-	716,000
500	500	1,914,000	-	-	603,000	-	-	834,000
600	500	2,242,000	-	-	714,000	-	-	973,000
700	600	2,954,000	-	-	854,000	-	-	-
800	600	3,472,000	-	-	946,000	-	-	-
900	600	4,131,000	-	-	1,015,000	-	-	-
1000	700	4,862,000	-	-	-	-	-	-

フランジアダプター



スリーブジョイント



単位:円

品名 口径	N型		S型	
	N-0	N-1	S-0	S-1
20	-	※	-	-
25	-	※	※	※
32	-	5,850	-	-
40	-	※	-	5,860
50	※	6,140	5,270	5,990
65	※	8,410	-	7,360
80	※	8,720	6,960	8,350
90	-	-	-	※
100	11,550	15,150	8,990	11,220
125	※	18,450	10,770	16,220
150	16,740	※	13,140	21,380
200	29,170	34,770	23,960	※
250	50,560	52,780	※	※
300	※	※	※	※
350	※	※	-	-
400	※	※	-	-
450	-	※	-	-
500	-	※	-	-

S-1型



単位:円

品名 口径	C型
	C-1
50	6,410
75	12,980
100	18,270
125	※
150	27,300
200	※
250	※
300	※

単位:円

品名 口径	G型		
	G-0	G	Gエポブルー
25	-	※	※
32	-	4,050	6,560
40	-	4,390	6,880
50	3,700	4,390	7,130
65	4,110	6,050	8,100
80	4,530	7,630	10,080
100	7,370	10,950	15,140
125	10,310	13,390	※
150	11,250	17,620	※
200	23,800	※	-
250	49,670	-	-
300	※	-	-

※印が付いた製品については、受注生産品の為別途お問い合わせ下さい