

10. 伸縮可撓管・ヴィクトリックジョイント

スーパーボール

コスモ工機(株)

ダクティル鋳鉄製ボール式伸縮可撓管 離脱防止性能A級(タイロッド付標準仕様)

GX形用

GX形受口 × GX形受口

■EB-UG × UG

単位: 円

呼び径	偏芯量(mm)			
	100	200	300	400
75	473,000	515,000	551,000	600,000
100	562,000	598,000	643,000	699,000
150	679,000	784,000	865,000	972,000
200	835,000	972,000	1,056,000	1,168,000
250	1,103,000	1,244,000	1,348,000	1,653,000
300	1,258,000	1,472,000	1,630,000	1,889,000
400	1,932,000	2,209,000	2,459,000	2,794,000

フランジ × GX形受口

■EB-F × UG

単位: 円

呼び径	偏芯量(mm)			
	100	200	300	400
75	367,000	409,000	454,000	481,000
100	454,000	495,000	535,000	578,000
150	572,000	677,000	756,000	838,000
200	725,000	859,000	941,000	1,027,000
250	911,000	1,065,000	1,188,000	1,452,000
300	1,052,000	1,267,000	1,423,000	1,601,000
400	1,599,000	1,842,000	2,135,000	2,420,000

GX形受口 × GX形挿口

■EB-UG × SG

単位: 円

呼び径	偏芯量(mm)			
	100	200	300	400
75	435,000	477,000	522,000	560,000
100	532,000	560,000	604,000	661,000
150	642,000	746,000	827,000	925,000
200	800,000	936,000	1,019,000	1,141,000
250	1,088,000	1,182,000	1,306,000	1,590,000
300	1,183,000	1,400,000	1,589,000	1,854,000
400	1,813,000	2,086,000	2,336,000	2,661,000

フランジ × GX形挿口

■EB-F × SG

単位: 円

呼び径	偏芯量(mm)			
	100	200	300	400
75	330,000	374,000	408,000	446,000
100	416,000	454,000	496,000	545,000
150	534,000	641,000	718,000	794,000
200	689,000	827,000	906,000	1,012,000
250	858,000	1,026,000	1,144,000	1,420,000
300	979,000	1,193,000	1,371,000	1,536,000
400	1,478,000	1,715,000	2,009,000	2,284,000

GX形挿口 × GX形挿口

■EB-SG × SG

単位: 円

呼び径	偏芯量(mm)			
	100	200	300	400
75	398,000	439,000	484,000	523,000
100	489,000	522,000	566,000	620,000
150	604,000	708,000	789,000	875,000
200	767,000	903,000	986,000	1,117,000
250	960,000	1,143,000	1,264,000	1,531,000
300	1,109,000	1,325,000	1,539,000	1,802,000
400	1,694,000	1,962,000	2,212,000	2,528,000

フランジ: 7. 5K仕様です。

1.0MPa以上のタイロッド付に関してはお問合せ下さい。

接合部付属品は含まれておりません。

ダクタイル鋳鉄製ボール式伸縮可撓管 離脱防止性能A級(タイロッド付標準仕様)

K形用

フランジ × フランジ

■EB-F × F

単位:円

呼び径	偏芯量(mm)				
	100	200	300	400	500
50	140,000	170,000	203,000	-	-
75	221,000	261,000	291,000	348,000	-
100	299,000	329,000	365,000	401,000	-
150	398,000	490,000	549,000	609,000	-
200	527,000	627,000	704,000	778,000	-
250	643,000	782,000	872,000	1,076,000	-
300	741,000	879,000	1,012,000	1,204,000	-
350	867,000	1,070,000	1,298,000	1,512,000	-
400	1,198,000	1,395,000	1,719,000	1,941,000	-
450	1,501,000	1,763,000	2,047,000	2,343,000	-
500	1,627,000	1,960,000	2,280,000	2,616,000	-
600	2,195,000	2,495,000	2,917,000	3,925,000	-
700	-	4,345,000	4,597,000	4,930,000	5,462,000
800	-	5,033,000	5,214,000	5,865,000	6,599,000
900	-	6,403,000	6,780,000	7,526,000	8,408,000
1000	-	9,916,000	10,524,000	11,177,000	12,260,000

フランジ × K形挿口

■EB-F × S

単位:円

呼び径	偏芯量(mm)				
	100	200	300	400	500
75	215,000	257,000	286,000	329,000	-
100	295,000	326,000	361,000	395,000	-
150	389,000	481,000	540,000	594,000	-
200	523,000	624,000	702,000	768,000	-
250	618,000	761,000	848,000	1,056,000	-
300	702,000	874,000	1,007,000	1,189,000	-
350	922,000	1,055,000	1,283,000	1,503,000	-
400	1,155,000	1,378,000	1,656,000	1,901,000	-
450	1,549,000	1,753,000	2,045,000	2,323,000	-
500	1,665,000	1,953,000	2,292,000	2,608,000	-
600	2,159,000	2,485,000	2,912,000	3,303,000	-
700	-	4,303,000	4,554,000	4,888,000	5,422,000
800	-	4,984,000	5,165,000	5,815,000	6,548,000
900	-	6,321,000	6,792,000	7,449,000	8,352,000
1000	-	9,842,000	10,465,000	11,137,000	12,289,000

フランジ × K形受口

■EB-F × U

呼び径	偏芯量(mm)				
	100	200	300	400	500
75	221,000	261,000	291,000	332,000	-
100	300,000	333,000	367,000	399,000	-
150	399,000	491,000	550,000	603,000	-
200	529,000	630,000	707,000	769,000	-
250	645,000	786,000	874,000	1,061,000	-
300	743,000	884,000	1,016,000	1,194,000	-
350	881,000	1,080,000	1,306,000	1,540,000	-
400	1,208,000	1,431,000	1,728,000	1,966,000	-
450	1,523,000	1,771,000	2,172,000	2,381,000	-
500	1,709,000	1,978,000	2,365,000	2,656,000	-
600	2,234,000	2,558,000	2,971,000	3,941,000	-
700	-	4,463,000	4,629,000	4,962,000	5,496,000
800	-	5,067,000	5,247,000	5,898,000	6,632,000
900	-	6,574,000	7,046,000	7,703,000	8,637,000
1000	-	10,142,000	10,766,000	11,437,000	12,622,000

※その他の口径についてはお問い合わせください。

フランジ: 7. 5K仕様です。

1.0MPa以上のタイロッド付に関してはお問合せ下さい。

接合部付属品は含まれておりません。

K形受口 × K形受口

■EB-U × U

単位:円

呼び径	偏芯量(mm)				
	100	200	300	400	500
75	221,000	261,000	291,000	315,000	-
100	301,000	334,000	369,000	398,000	-
150	409,000	492,000	551,000	598,000	-
200	540,000	632,000	709,000	761,000	-
250	662,000	791,000	880,000	1,045,000	-
300	762,000	903,000	1,018,000	1,186,000	-
350	931,000	1,088,000	1,315,000	1,575,000	-
400	1,231,000	1,440,000	1,730,000	1,998,000	-
450	1,574,000	1,814,000	2,122,000	2,408,000	-
500	1,765,000	2,032,000	2,339,000	2,710,000	-
600	2,274,000	2,576,000	3,024,000	3,453,000	-
700	-	4,495,000	4,662,000	4,996,000	5,529,000
800	-	5,198,000	5,282,000	5,931,000	6,666,000
900	-	6,745,000	7,312,000	7,879,000	8,865,000
1000	-	10,368,000	11,008,000	11,696,000	12,984,000

K形受口 × K形挿口

■EB-U × S

単位:円

呼び径	偏芯量(mm)				
	100	200	300	400	500
75	215,000	257,000	286,000	314,000	-
100	296,000	327,000	362,000	394,000	-
150	392,000	483,000	542,000	589,000	-
200	523,000	624,000	702,000	760,000	-
250	640,000	780,000	870,000	1,041,000	-
300	738,000	877,000	1,009,000	1,180,000	-
350	878,000	1,063,000	1,290,000	1,528,000	-
400	1,184,000	1,387,000	1,671,000	1,930,000	-
450	1,501,000	1,753,000	2,057,000	2,347,000	-
500	1,700,000	1,969,000	2,335,000	2,642,000	-
600	2,178,000	2,503,000	3,120,000	3,818,000	-
700	-	4,337,000	4,588,000	4,922,000	5,454,000
800	-	5,019,000	5,198,000	5,848,000	6,582,000
900	-	6,492,000	7,058,000	7,626,000	8,580,000
1000	-	10,068,000	10,707,000	11,397,000	12,651,000

K形挿口 × K形挿口

■EB-S × S

単位:円

呼び径	偏芯量(mm)				
	100	200	300	400	500
75	211,000	251,000	281,000	312,000	-
100	266,000	320,000	354,000	388,000	-
150	381,000	473,000	531,000	578,000	-
200	518,000	617,000	695,000	759,000	-
250	630,000	771,000	859,000	1,035,000	-
300	694,000	866,000	998,000	1,174,000	-
350	952,000	1,038,000	1,266,000	1,480,000	-
400	1,189,000	1,363,000	1,595,000	1,851,000	-
450	1,471,000	1,731,000	2,014,000	2,289,000	-
500	1,665,000	1,945,000	2,267,000	2,583,000	-
600	2,112,000	2,461,000	2,877,000	3,251,000	-
700	-	4,263,000	4,512,000	4,846,000	5,380,000
800	-	4,936,000	5,115,000	5,765,000	6,498,000
900	-	6,238,000	6,804,000	7,372,000	8,295,000
1000	-	9,768,000	10,406,000	11,097,000	12,318,000

※その他の口径についてはお問い合わせください。

フランジ: 7. 5K仕様です。

1.0MPa以上のタイロッド付に関してはお問合せ下さい。

接合部付属品は含まれておりません。

ダクタイル鋳鉄製ボール式伸縮可撓管 離脱防止性能A級(タイロッド付標準仕様)

NS形用

フランジ × NS形挿口

■EB-F × SN

単位:円

呼び径	偏芯量(mm)				
	100	200	300	400	500
75	287,000	325,000	355,000	388,000	-
100	362,000	395,000	431,000	474,000	-
150	464,000	557,000	624,000	690,000	-
200	599,000	719,000	788,000	880,000	-
250	746,000	892,000	995,000	1,235,000	-
300	851,000	1,037,000	1,192,000	1,336,000	-
350	990,000	1,220,000	1,440,000	1,694,000	-
400	1,299,000	1,520,000	1,800,000	2,166,000	-
450	1,697,000	1,897,000	2,256,000	2,662,000	-
500	1,928,000	2,237,000	2,550,000	2,821,000	-
600	2,469,000	2,845,000	3,221,000	3,546,000	-
700	-	4,740,000	5,180,000	5,665,000	6,308,000
800	-	5,705,000	6,209,000	6,614,000	8,076,000

NS形受口 × NS形挿口

■EB-UN × SN

呼び径	偏芯量(mm)				
	100	200	300	400	500
75	378,000	415,000	454,000	487,000	-
100	463,000	487,000	525,000	575,000	-
150	558,000	649,000	719,000	804,000	-
200	696,000	814,000	886,000	992,000	-
250	946,000	1,028,000	1,136,000	1,383,000	-
300	1,029,000	1,217,000	1,382,000	1,612,000	-
350	1,211,000	1,429,000	1,647,000	1,851,000	-
400	1,514,000	1,764,000	2,015,000	2,266,000	-
450	1,994,000	2,275,000	2,556,000	2,838,000	-
500	2,437,000	2,749,000	3,063,000	3,377,000	-
600	3,061,000	3,439,000	3,815,000	4,191,000	-
700	-	5,535,000	5,976,000	6,416,000	7,033,000
800	-	6,720,000	7,224,000	7,727,000	9,027,000

フランジ × NS形受口

■EB-F × UN

呼び径	偏芯量(mm)				
	100	200	300	400	500
75	319,000	356,000	395,000	418,000	-
100	395,000	430,000	465,000	503,000	-
150	497,000	589,000	657,000	729,000	-
200	630,000	747,000	818,000	893,000	-
250	792,000	926,000	1,033,000	1,263,000	-
300	915,000	1,102,000	1,237,000	1,392,000	-
350	1,084,000	1,292,000	1,521,000	1,738,000	-
400	1,416,000	1,665,000	1,916,000	2,166,000	-
450	1,817,000	2,077,000	2,380,000	2,662,000	-
500	2,195,000	2,509,000	2,821,000	3,135,000	-
600	2,786,000	3,164,000	3,540,000	3,916,000	-
700	-	5,226,000	5,666,000	6,105,000	8,117,000
800	-	6,111,000	6,614,000	7,117,000	8,484,000

NS形挿口 × NS形挿口

■EB-SN × SN

呼び径	偏芯量(mm)				
	100	200	300	400	500
75	346,000	382,000	421,000	455,000	-
100	425,000	454,000	492,000	539,000	-
150	525,000	616,000	686,000	761,000	-
200	667,000	785,000	857,000	971,000	-
250	835,000	994,000	1,099,000	1,331,000	-
300	964,000	1,152,000	1,338,000	1,567,000	-
350	1,128,000	1,346,000	1,564,000	1,782,000	-
400	1,398,000	1,597,000	1,899,000	2,149,000	-
450	1,870,000	2,080,000	2,418,000	2,714,000	-
500	2,165,000	2,479,000	2,792,000	3,063,000	-
600	2,744,000	3,120,000	3,496,000	3,873,000	-
700	-	5,049,000	5,489,000	5,930,000	6,521,000
800	-	6,315,000	6,818,000	7,322,000	8,601,000

NS形受口 × NS形受口

■EB-UN × UN

呼び径	偏芯量(mm)				
	100	200	300	400	500
75	411,000	448,000	479,000	522,000	-
100	489,000	520,000	559,000	608,000	-
150	590,000	682,000	752,000	845,000	-
200	726,000	845,000	918,000	1,016,000	-
250	959,000	1,064,000	1,172,000	1,437,000	-
300	1,094,000	1,280,000	1,417,000	1,643,000	-
350	1,293,000	1,512,000	1,730,000	1,948,000	-
400	1,631,000	1,881,000	2,131,000	2,381,000	-
450	2,118,000	2,399,000	2,680,000	2,962,000	-
500	2,708,000	3,021,000	3,335,000	3,649,000	-
600	3,380,000	3,757,000	4,134,000	4,510,000	-
700	-	6,022,000	6,461,000	6,901,000	7,623,000
800	-	7,126,000	7,629,000	8,131,000	9,494,000

※その他の口径についてはお問い合わせください。
フランジ: 7.5K仕様です。1.0MPa以上のタイロッド付に関してはお問合せ下
接合部付属品は含まれておりません。

※その他の口径についてはお問い合わせください。

フランジ: 7.5K仕様です。

1.0MPa以上のタイロッド付に関してはお問合せ下

接合部付属品は含まれておりません。

タイ・フレックス(TF-80W)GX形

大成機工(株)

単位:円

FCD製・伸縮可撓管

離脱防止性能A級

呼び径	接合形式	ダブル型(TF-80W)			
		偏心量100mm	偏心量200mm	偏心量300mm	偏心量400mm
75	F x U	349,000	396,000	443,000	490,000
	F x S	315,000	362,000	409,000	456,000
	U x U	476,000	523,000	570,000	617,000
	U x S	442,000	489,000	536,000	583,000
	S x S	408,000	455,000	502,000	549,000
100	F x U	420,000	482,000	544,000	606,000
	F x S	384,000	446,000	508,000	570,000
	U x U	559,000	621,000	683,000	745,000
	U x S	523,000	585,000	647,000	709,000
	S x S	487,000	549,000	611,000	673,000
150	F x U	569,000	661,000	753,000	845,000
	F x S	527,000	619,000	711,000	803,000
	U x U	719,000	811,000	903,000	995,000
	U x S	677,000	769,000	861,000	953,000
	S x S	635,000	727,000	819,000	911,000
200	F x U	703,000	827,000	951,000	1,075,000
	F x S	682,000	806,000	930,000	1,054,000
	U x U	881,000	1,005,000	1,129,000	1,253,000
	U x S	860,000	984,000	1,108,000	1,232,000
	S x S	839,000	963,000	1,087,000	1,211,000
250	F x U	880,000	1,036,000	1,192,000	1,348,000
	F x S	833,000	989,000	1,145,000	1,301,000
	U x U	1,107,000	1,263,000	1,419,000	1,575,000
	U x S	1,060,000	1,216,000	1,372,000	1,528,000
	S x S	1,013,000	1,169,000	1,325,000	1,481,000
300	F x U	1,023,000	1,210,000	1,397,000	1,584,000
	F x S	953,000	1,140,000	1,327,000	1,514,000
	U x U	1,311,000	1,498,000	1,685,000	1,872,000
	U x S	1,241,000	1,428,000	1,615,000	1,802,000
	S x S	1,171,000	1,358,000	1,545,000	1,732,000
400	F x U	1,602,000	1,852,000	2,102,000	2,352,000
	F x S	1,474,000	1,724,000	1,974,000	2,224,000
	U x U	1,986,000	2,236,000	2,486,000	2,736,000
	U x S	1,858,000	2,108,000	2,358,000	2,608,000
	S x S	1,730,000	1,980,000	2,230,000	2,480,000



ダブル型

※F=フランジ、U=受口(GX形)、S=挿口(GX形)

※上記価格には接合用附属品は含んでおりません。

※フランジ: 7.5K仕様、高圧使用の場合は別途お問合せ下さい。

タイ・フレックス(TF-80W)K形

大成機工(株)

単位:円

FCD製・伸縮可撓管

離脱防止性能A級

呼び径	接合形式	ダブル型(TF-80W)			
		偏心量100mm	偏心量200mm	偏心量300mm	偏心量400mm
50	F x F	141,000	172,000	203,000	—
75	F x F	222,000	269,000	316,000	363,000
	F x U	227,000	274,000	321,000	368,000
	F x S	219,000	266,000	313,000	360,000
	U x U	232,000	279,000	326,000	373,000
	U x S	224,000	271,000	318,000	365,000
	S x S	216,000	263,000	310,000	357,000
100	F x F	281,000	343,000	405,000	467,000
	F x U	283,000	345,000	407,000	469,000
	F x S	273,000	335,000	397,000	459,000
	U x U	285,000	347,000	409,000	471,000
	U x S	275,000	337,000	399,000	461,000
	S x S	265,000	327,000	389,000	451,000
150	F x F	419,000	511,000	603,000	695,000
	F x U	421,000	513,000	605,000	697,000
	F x S	404,000	496,000	588,000	680,000
	U x U	423,000	515,000	607,000	699,000
	U x S	406,000	498,000	590,000	682,000
	S x S	389,000	481,000	573,000	665,000
200	F x F	525,000	649,000	773,000	897,000
	F x U	538,000	662,000	786,000	910,000
	F x S	525,000	649,000	773,000	897,000
	U x U	551,000	675,000	799,000	923,000
	U x S	538,000	662,000	786,000	910,000
	S x S	525,000	649,000	773,000	897,000
250	F x F	653,000	809,000	965,000	1,121,000
	F x U	661,000	817,000	973,000	1,129,000
	F x S	645,000	801,000	957,000	1,113,000
	U x U	669,000	825,000	981,000	1,137,000
	U x S	653,000	809,000	965,000	1,121,000
	S x S	637,000	793,000	949,000	1,105,000
300	F x F	735,000	922,000	1,109,000	1,296,000
	F x U	753,000	940,000	1,127,000	1,314,000
	F x S	712,000	899,000	1,086,000	1,273,000
	U x U	771,000	958,000	1,145,000	1,332,000
	U x S	730,000	917,000	1,104,000	1,291,000
	S x S	689,000	876,000	1,063,000	1,250,000
350	F x F	894,000	1,112,000	1,330,000	1,548,000
	F x U	922,000	1,140,000	1,358,000	1,576,000
	F x S	875,000	1,093,000	1,311,000	1,529,000
	U x U	950,000	1,168,000	1,386,000	1,604,000
	U x S	903,000	1,121,000	1,339,000	1,557,000
	S x S	856,000	1,074,000	1,292,000	1,510,000
400	F x F	1,218,000	1,468,000	1,718,000	1,968,000
	F x U	1,243,000	1,493,000	1,743,000	1,993,000
	F x S	1,173,000	1,423,000	1,673,000	1,923,000
	U x U	1,268,000	1,518,000	1,768,000	2,018,000
	U x S	1,198,000	1,448,000	1,698,000	1,948,000
	S x S	1,128,000	1,378,000	1,628,000	1,878,000
450	F x F	1,556,000	1,838,000	2,120,000	2,402,000
	F x U	1,587,000	1,869,000	2,151,000	2,433,000
	F x S	1,521,000	1,803,000	2,085,000	2,367,000
	U x U	1,618,000	1,900,000	2,182,000	2,464,000
	U x S	1,552,000	1,834,000	2,116,000	2,398,000
	S x S	1,486,000	1,768,000	2,050,000	2,332,000

※F=フランジ、U=受口、S=挿口(K型、T型)

呼び径	接合形式	ダブル型(TF-80W)			
		偏心量100mm	偏心量200mm	偏心量300mm	偏心量400mm
500	F x F	1,732,000	2,045,000	2,358,000	2,671,000
	F x U	1,779,000	2,092,000	2,405,000	2,718,000
	F x S	1,714,000	2,027,000	2,340,000	2,653,000
	U x U	1,826,000	2,139,000	2,452,000	2,765,000
	U x S	1,761,000	2,074,000	2,387,000	2,700,000
	S x S	1,696,000	2,009,000	2,322,000	2,635,000
600	F x F	2,253,000	2,629,000	3,005,000	3,381,000
	F x U	2,296,000	2,672,000	3,048,000	3,424,000
	F x S	2,220,000	2,596,000	2,972,000	3,348,000
	U x U	2,339,000	2,715,000	3,091,000	3,467,000
	U x S	2,263,000	2,639,000	3,015,000	3,391,000
	S x S	2,187,000	2,563,000	2,939,000	3,315,000
700	F x F	—	4,509,000	4,949,000	5,389,000
	F x U	—	4,584,000	5,024,000	5,464,000
	F x S	—	4,464,000	4,904,000	5,344,000
	U x U	—	4,659,000	5,099,000	5,539,000
	U x S	—	4,539,000	4,979,000	5,419,000
	S x S	—	4,419,000	4,859,000	5,299,000
800	F x F	—	5,233,000	5,737,000	6,241,000
	F x U	—	5,331,000	5,835,000	6,339,000
	F x S	—	5,171,000	5,675,000	6,179,000
	U x U	—	5,429,000	5,933,000	6,437,000
	U x S	—	5,269,000	5,773,000	6,277,000
	S x S	—	5,109,000	5,613,000	6,117,000
900	F x F	—	6,488,000	7,055,000	7,622,000
	F x U	—	6,648,000	7,215,000	7,782,000
	F x S	—	6,391,000	6,958,000	7,525,000
	U x U	—	6,808,000	7,375,000	7,942,000
	U x S	—	6,551,000	7,118,000	7,685,000
	S x S	—	6,294,000	6,861,000	7,428,000
1000	F x F	—	10,017,000	10,650,000	11,283,000
1100	F x F	—	—	—	13,919,000
1200	F x F	—	—	—	16,839,000
1350	F x F	—	—	—	21,172,000
1500	F x F	—	—	—	24,339,000

タイ・フレックス(TF-80W) NS形

大成機工(株)

FCD製・伸縮可撓管

離脱防止性能A級

単位:円

呼び径	接合形式	ダブル型(TF-80W)				呼び径	接合形式	ダブル型(TF-80W)			
		偏心量100mm	偏心量200mm	偏心量300mm	偏心量400mm			偏心量100mm	偏心量200mm	偏心量300mm	偏心量400mm
75	F x U	313,000	360,000	407,000	454,000	500	F x U	2,244,000	2,557,000	2,870,000	3,183,000
	F x S	282,000	329,000	376,000	423,000		F x S	1,973,000	2,286,000	2,599,000	2,912,000
	U x U	404,000	451,000	498,000	545,000		U x U	2,756,000	3,069,000	3,382,000	3,695,000
	U x S	373,000	420,000	467,000	514,000		U x S	2,485,000	2,798,000	3,111,000	3,424,000
	S x S	342,000	389,000	436,000	483,000		S x S	2,214,000	2,527,000	2,840,000	3,153,000
100	F x U	376,000	438,000	500,000	562,000	600	F x U	2,847,000	3,223,000	3,599,000	3,975,000
	F x S	343,000	405,000	467,000	529,000		F x S	2,528,000	2,904,000	3,280,000	3,656,000
	U x U	471,000	533,000	595,000	657,000		U x U	3,441,000	3,817,000	4,193,000	4,569,000
	U x S	438,000	500,000	562,000	624,000		U x S	3,122,000	3,498,000	3,874,000	4,250,000
	S x S	405,000	467,000	529,000	591,000		S x S	2,803,000	3,179,000	3,555,000	3,931,000
150	F x U	509,000	601,000	693,000	785,000	700	F x U	-	5,304,000	5,744,000	6,184,000
	F x S	471,000	563,000	655,000	747,000		F x S	-	4,818,000	5,258,000	5,698,000
	U x U	599,000	691,000	783,000	875,000		U x U	-	6,099,000	6,539,000	6,979,000
	U x S	561,000	653,000	745,000	837,000		U x S	-	5,613,000	6,053,000	6,493,000
	S x S	523,000	615,000	707,000	799,000		S x S	-	5,127,000	5,567,000	6,007,000
200	F x U	628,000	752,000	876,000	1,000,000	800	F x U	-	6,248,000	6,752,000	7,256,000
	F x S	609,000	733,000	857,000	981,000		F x S	-	5,843,000	6,347,000	6,851,000
	U x U	731,000	855,000	979,000	1,103,000		U x U	-	7,263,000	7,767,000	8,271,000
	U x S	712,000	836,000	960,000	1,084,000		U x S	-	6,858,000	7,362,000	7,866,000
	S x S	693,000	817,000	941,000	1,065,000		S x S	-	6,453,000	6,957,000	7,461,000
250	F x U	786,000	942,000	1,098,000	1,254,000	900	F x U	-	7,792,000	8,359,000	8,926,000
	F x S	743,000	899,000	1,055,000	1,211,000		F x S	-	7,143,000	7,710,000	8,277,000
	U x U	919,000	1,075,000	1,231,000	1,387,000		U x U	-	9,096,000	9,663,000	10,230,000
	U x S	876,000	1,032,000	1,188,000	1,344,000		U x S	-	8,447,000	9,014,000	9,581,000
	S x S	833,000	989,000	1,145,000	1,301,000		S x S	-	7,798,000	8,365,000	8,932,000
300	F x U	913,000	1,100,000	1,287,000	1,474,000	1000	F x U	-	11,911,000	12,544,000	13,177,000
	F x S	849,000	1,036,000	1,223,000	1,410,000		F x S	-	11,032,000	11,665,000	12,298,000
	U x U	1,091,000	1,278,000	1,465,000	1,652,000		U x U	-	13,805,000	14,438,000	15,071,000
	U x S	1,027,000	1,214,000	1,401,000	1,588,000		U x S	-	12,926,000	13,559,000	14,192,000
	S x S	963,000	1,150,000	1,337,000	1,524,000		S x S	-	12,047,000	12,680,000	13,313,000
350	F x U	1,102,000	1,320,000	1,538,000	1,756,000	400	F x U	1,434,000	1,684,000	1,934,000	2,184,000
	F x S	1,020,000	1,238,000	1,456,000	1,674,000		F x S	1,317,000	1,567,000	1,817,000	2,067,000
	U x U	1,310,000	1,528,000	1,746,000	1,964,000		U x U	1,650,000	1,900,000	2,150,000	2,400,000
	U x S	1,228,000	1,446,000	1,664,000	1,882,000		U x S	1,533,000	1,783,000	2,033,000	2,283,000
	S x S	1,146,000	1,364,000	1,582,000	1,800,000		S x S	1,416,000	1,666,000	1,916,000	2,166,000
450	F x U	1,856,000	2,138,000	2,420,000	2,702,000	500	F x U	2,244,000	2,557,000	2,870,000	3,183,000
	F x S	1,732,000	2,014,000	2,296,000	2,578,000		F x S	1,973,000	2,286,000	2,599,000	2,912,000
	U x U	2,156,000	2,438,000	2,720,000	3,002,000		U x U	2,756,000	3,069,000	3,382,000	3,695,000
	U x S	2,032,000	2,314,000	2,596,000	2,878,000		U x S	2,485,000	2,798,000	3,111,000	3,424,000
	S x S	1,908,000	2,190,000	2,472,000	2,754,000		S x S	2,214,000	2,527,000	2,840,000	3,153,000

※F=フランジ、U=受口、S=挿口(K型、T型)

品名	スリーブジョイント (エポキシ樹脂粉体塗装)			クローザージョイント				フランジアダプター	
	VD型	VDL型	RD型	CL-A 標準型 (両ベベル)		CL-A100mm偏心型 (両ベベル)		FA-CB型両フランジ	
ボルト SUS304				両間	価格	両間	価格	両間	価格
サイズ									
50	－	－	－	－	－	－	－	500	392,000
65	74,460	96,900	－	－	－	－	－	500	426,000
80	86,700	108,000	－	800	423,000	1150	503,900	500	447,000
100	100,980	123,400	－	800	452,000	1150	526,000	500	480,000
125	130,600	162,000	－	800	504,000	1150	589,000	500	530,000
150	160,200	196,900	－	800	555,000	1150	644,000	500	572,000
200	194,900	253,000	－	800	598,000	1150	701,000	500	657,000
250	227,000	279,500	－	800	683,000	1150	810,000	500	726,000
300	248,900	313,200	－	800	816,000	1600	922,000	500	804,000
350	－	－	369,000	800	892,000	1600	1,042,000	500	914,000
400	－	－	434,500	800	1,057,000	1600	1,189,000	500	1,020,000
450	－	－	480,000	800	1,212,000	1600	1,368,000	500	1,152,000
500	－	－	558,000	900	1,373,000	1700	1,570,000	500	1,307,000
600	－	－	650,000	900	1,625,000	1700	1,825,000	500	1,535,000
700	－	－	－	1000	1,972,000	1800	2,181,000	600	2,036,000
800	－	－	－	1100	2,325,000	1800	2,633,000	600	2,393,000
900	－	－	－	1100	2,625,000	1800	2,900,000	600	2,852,000
1000	－	－	－	1200	3,376,000	1900	3,722,000	700	3,442,000

品名	クローザージョイント(低圧用)		ヴィクトリック ジョイント(本体のみ)					
	Σ 0両ベベル100mm偏心型		S型		N型		フラタイト	補修ジョイント
	面間	価格	S-0	S-1	N-0	N-1	FT	RJ
20	-	-	-	3,460	-	3,540	-	-
25	-	-	2,820	3,650	-	3,790	-	52,170
32	-	-	-	3,920	-	4,060	-	-
40	-	-	-	4,110	-	4,240	-	58,340
50	950	166,000	3,650	4,200	4,120	4,300	9,740	62,490
65	-	-	-	4,920	4,920	5,840	10,900	83,410
80	950	217,300	4,300	5,850	5,550	6,110	14,610	104,210
100	950	248,900	6,620	7,360	8,510	10,620	21,030	125,100
125	950	288,700	7,930	11,940	9,790	13,580	25,540	135,590
150	950	369,300	9,670	15,740	12,320	16,120	29,990	145,900
200	1000	393,000	17,630	26,070	21,470	25,590	-	167,000
250	1000	525,300	35,460	42,620	37,220	38,870	-	232,800
300	1000	589,600	38,250	55,140	44,450	50,760	-	251,320
350	1050	641,600	-	-	49,060	83,500	-	-
400	1050	709,000	-	-	95,440	104,400	-	-
450	1050	803,800	-	-	-	116,320	-	-
500	1100	881,300	-	-	-	120,420	-	-
600	1150	1,072,000	-	-	-	-	-	-
700	1200	1,211,000	-	-	-	-	-	-
800	1200	1,455,000	-	-	-	-	-	-
900	1200	1,750,000	-	-	-	-	-	-
1000	1200	2,039,000	-	-	-	-	-	-

単位:円

品名	N-0(ナイロンコーティング)				N-1(ナイロンコーティング)			
ゴムリング	SBR		EPDM		SBR		EPDM	
ボルト	S25C	SUS304	S25C	SUS304	S25C	SUS304	S25C	SUS304
口径 50	7,740	10,350	8,870	11,480	7,870	10,860	9,010	11,970
65	9,130	11,740	10,420	13,040	10,090	13,400	11,430	14,740
80	10,220	12,950	11,740	14,470	10,690	14,010	12,260	15,530
100	15,450	19,020	17,510	21,070	17,450	22,840	19,500	24,890
125	18,040	21,610	20,320	23,890	21,570	27,230	23,860	29,530
150	21,500	25,520	24,030	28,060	25,120	31,080	27,630	33,570
200	33,090	39,030	37,290	43,230	38,310	46,290	42,480	50,460
250	50,690	58,410	56,400	64,120	53,910	62,460	59,640	68,180
300	60,790	69,070	67,840	76,120	68,680	81,370	75,710	88,410

単位:円

品名	S-0(ナイロンコーティング)				S-1(ナイロンコーティング)			
ゴムリング	SBR		EPDM		SBR		EPDM	
ボルト	S25C	SUS304	S25C	SUS304	S25C	SUS304	S25C	SUS304
口径 50	7,250	9,870	8,380	11,000	7,780	10,720	8,890	11,830
65	-	-	-	-	9,130	12,230	10,420	13,520
80	9,020	11,740	10,540	13,260	10,420	13,740	11,990	15,310
100	13,700	17,270	15,770	19,330	14,890	18,460	16,940	20,520
125	16,250	19,830	18,520	22,100	20,050	25,740	22,320	28,020
150	19,030	23,040	21,560	25,550	24,710	30,680	27,220	33,190
200	30,810	36,760	35,010	40,950	38,720	46,700	42,910	50,890
250	50,750	58,460	56,450	64,180	57,460	66,000	63,180	71,730
300	56,980	65,270	64,000	72,290	72,820	85,500	79,870	92,560

単位:円

品名	NL(ナイロンコーティング)			
ゴムリング	SBR		EPDM	
ボルト	S25C	SUS304	S25C	SUS304
口径 50	8,460	11,560	9,630	12,730
65	10,880	14,350	12,240	15,710
80	11,560	15,030	13,140	16,800
100	18,770	24,400	20,930	26,570
125	23,300	29,530	25,650	31,880
150	27,100	33,630	29,750	36,260
200	41,440	49,810	45,840	54,190
250	58,380	67,340	64,400	73,370
300	74,460	88,080	81,820	95,440

単位:円

SUS304製部品		
品名 口径	Sカラー 1本	Nリング 1本
40	7,420	1,720
50	7,670	1,720
65	9,990	2,120
80	9,990	2,470
100	13,290	4,220
125	14,820	5,060
150	18,680	5,890
200	23,800	7,950
250	30,680	10,230
300	44,990	12,370